# **SILIGAINE® 15C5-E**

Expandable -60 °C to +250 °C Classes H and C

FIBREGLASS BRAIDED SLEEVING WITH SILICONE RUBBER COATING

### Standards\*

IEC 60684-1 and 60684-2.IEC 60684-3 part 400 to 402.

## **Applications**

Internal cabling for rotating machines classes H and C (motors, alternators, generators, transformers, inductors, etc.).
 All insulations up to 250°C permanent in the electric and electronic constructions, heating appliances, lighting, automobile, measuring, control, etc.

## **Options**

Other diameters: contact us.Other colours: contact us.

• Sleevings cut to length: contact us.

## **Packaging**

- Diameters from 0.5 to 1.5 mm: 200 m rolls.
  Diameters from 2 to 4 mm: 100 m rolls.
  - $\bullet$  Diameters from 5 to 16 mm: 50 m rolls.

# ELECTRIC INSULATING SLEEVINGS CLASS H and C SILICONE RUBBER COATING



## Characteristics General

- Continuous operating temperature: -60 °C to +250 °C.
- Expandable up to about twice the nominal diameter.
- Good resistance to humidity, ozone and UV.
- Good resistance to common chemical environments.
- Compatible with most impregnation varnishes class H.
- Self-extinguishing meets the requirements of test VW-1 as per standard UL 1441.
- Very good flexibility.
- Halogen-free.

### **Electrical**

• Dielectric strength (dry): > 5 kV.

## **Standard products**

Colour: black.

#### INTERNAL DIAMETER

1	-5	•	-5	_
	•	•	•	-

Nominal value (mm)	Minimum wall thickness (mm)	Approximate linear weight (kg/km)
0.5	0.25	2.6
1	0.25	5.1
1.5	0.35	7.7
2	0.35	10.2
2.5	0.40	12.7
3	0.40	15.2
4	0.50	20.1
5	0.50	24.9
6	0.50	29.6
7	0.50	34.2
8	0.50	38.7
10	0.65	47.6
12	0.65	56.0
14	0.65	64.1
16	0.65	71.9

<sup>\*</sup>Standards: our products comply with all or part of the requirements of standards quoted; contact us

### For this product, please contact:

OMERIN division principale 🗹

Zone Industrielle - F 63600 Ambert Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10 omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devey - F 42000 Saint-Étienne Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00 silisol@omerin.com



### www.omerin.com

® Registered trademark of the OMERIN Group. All information is indicative and may be modified without prior notice. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.