

HIGH TEMPERATURE WIRES AND CABLES FOR THE GENERAL MARKET SECTION III: COMPOSITE INSULATIONS

SILICABLE® VS -60 °C to +280 °C



Approvals - standards

- VERITAS approval certificates:
 - > No. BV 153552.
 - > No. BV 256192.
 - > No. BV 256096 – 2 hours at 400 °C.

Applications

- Cabling for heating resistors, cartridges, bands and plates.
- Cabling for domestic electrical heating appliances: kitchens, professional ovens, etc.
- Machines for thermoplastics or rubber.
- Industrial furnaces and air ovens.

Options

- Solid bare copper core – class 1 as per IEC 60228: ref. RVS (see details of this option below).
- Tin-plated copper core: ref. EVS.
- Reduced outer diameters: ref. VSL.
- Other nominal cross-sections: contact us.
- Other nominal stranding: contact us.
- Other options: contact us.

UNIPOLAR WIRES AND CABLES WITH COMPOSITE INSULATION



- 1 • Flexible bare copper core - class 5 as per IEC 60228.
- 2 • Impregnated fiberglass lappings.
- 3 • Silicone-coated fiberglass braid.

Characteristics

General

- Continuous operating temperatures: -60 °C to +280 °C.
- Good resistance to thermal shock.

Electrical

- Rated voltage: 300/500 V.
- Test voltage: 2000 V.

Standard products

- Standard colour: brown.
- Other colours on request including yellow/green.

VS

Flexible core • Class 5 as per IEC 60228

Nominal cross-section (mm²)	Nominal stranding	Maximum linear resistance at 20 °C (Ω/km)
0.25*	8 x 0.20	78.9
0.5	16 x 0.20	39.0
0.75	24 x 0.20	26.0
1	32 x 0.20	19.5
1.5	30 x 0.25	13.3
2.5	50 x 0.25	7.98
4	56 x 0.30	4.95
6	84 x 0.30	3.30
10	80 x 0.40	1.91
16	126 x 0.40	1.21
25	196 x 0.40	0.780
35	276 x 0.40	0.554
50	396 x 0.40	0.386
70	360 x 0.50	0.272
95	485 x 0.50	0.206
120	608 x 0.50	0.161
150	756 x 0.50	0.129
185	944 x 0.50	0.106
240	1221 x 0.50	0.0801

INSULATED WIRE OR CABLE

Nominal diameter (mm)	Approximate linear weight (kg/km)
1.9	5.7
2.1	8.8
2.4	11.9
2.5	14.5
2.8	19.1
3.2	29.3
4.0	47.4
4.6	67.5
6.6	106
7.9	192
10.0	302
12.0	395
13.4	556
16.3	785
18.0	1032
19.5	1278
22.5	1629
24.4	1957
27.5	2569

Option • RVS

Solid core • Class 1 as per IEC 60228

Nominal cross-section (mm²)	Nominal diameter (mm)	Maximum linear resistance at 20 °C (Ω/km)
0.5	1 x 0.80	36.0
0.75	1 x 0.98	24.5
1	1 x 1.13	18.1
1.5	1 x 1.38	12.1
2.5	1 x 1.77	7.41
4	1 x 2.24	4.61
6	1 x 2.76	3.08

INSULATED WIRE

Nominal diameter (mm)	Approximate linear weight (kg/km)
2.1	9.0
2.3	11.3
2.4	14.3
2.6	19.4
3.0	29.1
3.8	47.5
4.3	68.8

* Nominal cross-section not described in IEC 60228.

For this product, please contact:

OMERIN division principale ✓

Zone Industrielle - F 63600 Ambert

Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10

omerin@omerin.com

OMERIN division silisol □

BP 87 - ZI du Devey - F 42000 Saint-Etienne

Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00

silisol@omerin.com

omerin
LES CABLES DE L'EXTREME

www.omerin.com

® Registered trademark of the OMERIN Group. All information is indicative and may be modified without prior notice. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.