

HIGH TEMPERATURE WIRES AND CABLES FOR THE GENERAL MARKET SECTION III: COMPOSITE INSULATIONS

SILICABLE® BM-NVS

-60 °C to +350 °C



Approvals - standards

- Nickel type 200, as per standards ASTM B160, DIN 17753 and DIN 17740.
- Halogen-free: IEC 60754-1 / EN 50267-2-1.
 - Resistance to vertical flame propagation for an insulated cable: IEC 60332-1-2 / EN 50265-2-1 / NF C 32-070 test C2.
- VERITAS approval certificate No. BV.153552.

Applications

- Cabling for heating resistors, cartridges, bands and plates.

Options

- Nickel-plate copper earth wire core: Ref. BM-(NVS+CNVS).
- Class 5 flexible cores as per IEC 60228: contact us.
- Other nominal cross-sections: contact us.
- Other numbers of conductors: contact us.
- Cable without an earth wire: contact us.
 - Other options and/or combinations of the options outlined above: contact us.

MULTI-CONDUCTOR WIRES AND CABLES WITH COMPOSITE INSULATION



- 1 • Stranded nickel core
- 2 • Silicone impregnated fiberglass lappings.
- 3 • Silicone-coated fiberglass braid.
- 4 • Galvanised steel braid.

Characteristics General

- Continuous operating temperatures: -60 °C to +350 °C.
- Good resistance to thermal shocks and oxidization of core.
- Excellent ageing.

Electrical

- Rated voltage: 300/500 V.
- Test voltage: 2000 V.

Standard products

- Standard conductor colours: see table below.

Number	Colours
3	Yellow/Green – Blue – Brown
4	Yellow/Green – Brown – Black – Blue
5	Yellow/Green – Blue – Brown – Black – Grey

- Outer braid with or without coloured spiral stripe.
- Some cables may include a fiberglass tape or other separating tape under the outer braid.

For this product, please contact:

OMERIN division principale ✓

Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

OMERIN division silisol □

BP 87 - ZI du Devey - F 42000 Saint-Etienne
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00
silisol@omerin.com

omerin
LES CABLES DE L'EXTREME

www.omerin.com

® Registered trademark of the OMERIN Group. All information is indicative and may be modified without prior notice. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

Conducting core

INSULATED CONDUCTORS

SHEATHED CABLE

Nominal cross-section (mm ²)	Nominal stranding	Maximum linear resistance at 20 °C (Ω/km)	Nominal thickness of insulation (mm)	Nominal diameter of the conductor (mm)	Nominal diameter of the cable (mm)	Approximate linear weight (kg/km)
3 G 0.5	7 x 0.30	229	0.6	2.1	5.5	63.8
4 G 0.5	7 x 0.30	229	0.6	2.1	6.1	82.2
5 G 0.5	7 x 0.30	229	0.6	2.1	6.7	97.0
3 G 0.75	11 x 0.30	156	0.6	2.4	6.2	68.5
4 G 0.75	11 x 0.30	156	0.6	2.4	6.8	87.9
5 G 0.75	11 x 0.30	156	0.6	2.4	7.5	104
3 G 1	14 x 0.30	115	0.6	2.5	6.4	80.6
4 G 1	14 x 0.30	115	0.6	2.5	7.0	97.7
5 G 1	14 x 0.30	115	0.6	2.5	7.7	115
3 G 1.5	21 x 0.30	77.2	0.6	2.8	7.0	95.7
4 G 1.5	21 x 0.30	77.2	0.6	2.8	7.7	117
5 G 1.5	21 x 0.30	77.2	0.6	2.8	8.6	153
3 G 2.5	35 x 0.30	47.2	0.6	3.2	7.9	139
4 G 2.5	35 x 0.30	47.2	0.6	3.2	8.7	168
5 G 2.5	35 x 0.30	47.2	0.6	3.2	9.7	206
3 G 4	56 x 0.30	31.5	0.8	4.0	10.4	219
4 G 4	56 x 0.30	31.5	0.8	4.0	11.5	267
5 G 4	56 x 0.30	31.5	0.8	4.0	12.6	318
3 G 6	84 x 0.30	21.0	0.8	4.6	11.5	249
4 G 6	84 x 0.30	21.0	0.8	4.6	12.6	334
5 G 6	84 x 0.30	21.0	0.8	4.6	14.2	412
3 G 10	140 x 0.30	12.1	1.2	6.6	15.8	512
4 G 10	140 x 0.30	12.1	1.2	6.6	17.6	619

For this product, please contact:

OMERIN division principale 

Zone Industrielle - F 63600 Ambert

Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10

omerin@omerin.com

OMERIN division silisol 

BP 87 - ZI du Devey - F 42000 Saint-Étienne

Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00

silisol@omerin.com